

## (19) United States

# (12) Patent Application Publication (10) Pub. No.: US 2003/0088051 A1 Shimoda et al.

May 8, 2003 (43) Pub. Date:

### (54) PROCESS FOR PREPARING POLYCARBONATE AND APPARATUS FOR PREPARING POLYCARBONATE

### Inventors: Tomoaki Shimoda, Ichihara City (JP); Akio Ikeda, Ichihara City (JP); Takato Kimura, Ichihara City (JP); Ken Tamada, Ichihara City (JP); Hans-Peter Brack, Herrliberg (CH); Dennis Karlik, Bergen op Zoom (NL); Lina Prada, Murcia (ES); Hendricus Franciscus Zirkzee, Schore (NL); James Anthony Cella, Clifton Park,

NY (US)

Correspondence Address: CANTOR COLBURN, LLP **55 GRIFFIN ROAD SOUTH BLOOMFIELD, CT 06002** 

(73) Assignee: General Company, Electric

Schenectady, NY

10/063,282 Appl. No.:

(30)

(22)Filed: Apr. 8, 2002

(JP) ...... 2001-217251

Foreign Application Priority Data

#### **Publication Classification**

(51)	Int. Cl. <sup>7</sup>	 <b>64/00</b>
(52)	U.S. Cl.	 3/196

#### ABSTRACT (57)

A process for preparing an end-capped polycarbonate comprises melt reacting an aromatic dihydroxy compound, a carbonic acid diester, and optionally a catalyst in a prepolymerization vessel to form a polycarbonate product; transferring the polycarbonate product from the prepolymerization vessel; mixing the polycarbonate product with an endcapping agent under hermetic seal at a pressure of at least about 760 mm Hg; and transferring the polycarbonate product and end-capping agent mixture to a postpolymerization vessel to endcap the polycarbonate product. An apparatus for preparing an end-capped polycarbonate comprises a prepolymerization vessel having and inlet and an outlet; a postpolymerization vessel having an inlet and an outlet; a mixer in fluid communication with the outlet of the prepolymerization vessel and the inlet of the postpolymerization vessel; and a charging port through which an end-capping agent is charged to the mixer, wherein the mixer is hermetically sealed at greater than or equal to 760 mm Hg.